

# Body and Frame Alignment Systems Selector Guide



*Speed*



*Quick 42*



*BenchRack, 4200 - 6300*



*Mark 6*



Model	Speed	Mark 6	Quick 42	BenchRack 4200-6300
<b>Description</b>	Multifunctional platform for effective repair of cosmetic body work	A mobile bench system with the convenience of drive over mounting and optional mobility	Optimized platform for light cosmetic and heavy straightening repair with drive on capability and optional mobility	A universal collision repair system for both cosmetic and structural repair for any type of vehicle
<b>Segment</b>	Cars and small SUVs	Cars and SUVs	Cars and SUVs	Cars, light trucks, SUVs
<b>Pulling force per Draw Aligner</b>	5 tons	10 tons	10 tons	10 tons
<b>Platform length</b>	2510 mm	4060 mm	4200 mm	4200, 5000, 5500, 6300 mm
<b>Platform width</b>	766 mm (950 with arms)	900 mm	1110 mm	1175 mm
<b>Platform width with ramps attached</b>	–	–	1915 mm	2020 mm (2240 mm wide ramps)
<b>Minimum height</b>	104 mm	210 mm (270 mm top of cylinder)	480 mm	400 mm
<b>Maximum height (Floor to top of platform)</b>	1600 mm	1360 mm	1480 mm	1190 mm
<b>Maximum length with Draw Aligner</b>	3600 mm	5180 mm	5320 mm	Bench length + 1120 mm
<b>Maximum width with Draw Aligner</b>	2486 mm	2020 mm	2230 mm	2295 mm
<b>Work Area size Draw Aligner on both sides</b>	N/A	3140 mm	3550 mm	3415 mm
<b>Lift Capacity (Maximum vehicle weight)</b>	2500 kg / 5500 lbs	2800 kg / 6160 lbs	3000 kg / 6600 lbs	4200 kg / 9200 lbs
<b>Weight with lift, platform</b>	600 kg / 1371 lbs	680 kg / 1496 lbs	755 kg / 1661 lbs	950 – 1300 kg 2090 – 2860 lbs
<b>360° pulling capability</b>	Yes	Yes	Yes	Yes
<b>Mobile capability</b>	N/A	Yes (optional)	Yes (optional)	N/A
<b>In ground capability</b>	Yes	Yes	Yes	Yes
<b>Maximum height in ground</b>			1000 mm	
<b>Lift capacity in ground (Maximum vehicle weight)</b>	2500 kg / 5500 lbs	2800 kg / 6160 lbs	3000 kg / 6600 lbs	4200 kg / 9200 lbs
<b>Modular with measuring system</b>	Yes	Yes	Yes	Yes
<b>Modular with EVO system</b>	N/A	Yes	Yes	Yes
<b>Automatic tilt function</b>	N/A	N/A	Yes	N/A
<b>Loading angle</b>	N/A	N/A	Bench 3,5° Driving ramps 12°	Bench 2,6° Driving ramps 12°
<b>Milled surface for measuring</b>	N/A	Yes	Yes	Yes
<b>Remote control / Energy supply</b>	N/A	N/A	Yes	N/A
<b>Power</b>	3 phase, 50 Hz, 200/220/400 V – 1 phase, 60 Hz, 110/220 V			